





















Globally reliable





# NEWSLETTER V0/2














	ccm 						IN/EX	QTY	Info	Pos.	
G4FA	1396	4	66-80 KW 90-109 PS	ACCENT IV 1.4 i20 1.4 i30 1.4 ix20 1.4	11/10 - 09/08 - 12/15 12/11 - 12/15 11/10 -	77,00	56 2400 0000 57 2400 0000	IN EX	8 8		1
G4FC	1591	4	84-93 KW 114-126 PS	ACCENT IV 1.6 ELANTRA 1.6 CVVT i20 1.6 i30 1.6 ix20 1.6	10/11 - 06/06 - 06/11 09/08 - 12/12 01/12 - 12/06 11/10 -	77,00	56 2400 0000 57 2400 0000	IN EX	8 8		1
G4FD	1591	4	97-103 KW 132-140 PS	i30 1.6 GDI i40 1.6 GDI ix35 1.6 TUCSON 1.6 GDI VELOSTER 1.6 GDI	12/11 - 12/16 07/11 - 11/10 - 06/15 - 03/11 -	77,00	56 2400 0000 57 2400 0000	IN EX	8 8		1

	IN/EX			Material Specification	Valve Stem Coating	Cotter Design	Seat Treatment	Tip Treatment
<b>1</b>								
	IN	56 2400 0000	L = 93,20 D = 31,50 d = 5,48 a = 45°	S	NT			H
	EX	57 2400 0000	L = 92,60 D = 26,00 d = 5,47 a = 45°	A	NT			

	ccm 						IN/EX	QTY	Info	Pos.	
G4FA	1396	4	73-80 KW 10-109 PS	CEE'D 1.4 PRO CEE'D 1.4 CVVT RIO III 1.4 CVVT	10/10 - 12/12 02/08 - 09/12 09/11 -	77,00	56 2400 0000 57 2400 0000	IN EX	8 8		1
G4FC	1591	4	77-97 KW 105-132 PS	CARENS III 1.6 CVVT CEE'D 1.6 CVVT CERATO 1.6 PRO CEE'D 1.6 SOUL 1.6 CVVT VENGA 1.6 CVVT	08/09 - 12/06 - 05/06 - 02/08 - 02/09 - 02/10 -	77,00	56 2400 0000 57 2400 0000	IN EX	8 8		1
G4FD	1591	4	97-103 KW 132-140 PS	CARENS 1.6 GDi CEE'D 1.6 GDI K3 1.6 GDI RIO III 1.6 SOUL 1.6 GDI SPORTAGE 1.6 GDI	03/13 - 05/12 - 09/12 - 09/11 - 02/11 - 02/11 -	77,00	56 2400 0000 57 2400 0000	IN EX	8 8		1

	IN/EX			Material Specification	Valve Stem Coating	Cotter Design	Seat Treatment	Tip Treatment
<b>1</b>								
	IN	56 2400 0000	L = 93,20 D = 31,50 d = 5,48 a = 45°	S	NT			H
	EX	57 2400 0000	L = 92,60 D = 26,00 d = 5,47 a = 45°	A	NT			

	ccm 						IN/EX	QTY	Info	Pos.	
16 NZR	1598	4	55 KW 75 PS	ASTRA F 1.6	09/95 - 09/98	79,00	56 1405 0000 57 1405 0000	IN EX	4 4		1
C 16 NZ	1598	4	55 KW 75 PS	ASTRA F 1.6 i CORSA A CC 1.6 GSI	09/91 - 01/98 08/88 - 09/92	79,00	56 1405 0000 57 1405 0000	IN EX	4 4		1
C 16 SE	1598	4	74 KW 101 PS	ASTRA F 1.6 Si CORSA A CC 1.6 GSI Cat	03/92 - 12/94 02/92 - 03/93	79,00	56 1405 0000 57 1405 0000	IN EX	4 4		1
E 16 SE	1598	4	74 KW 100 PS	CORSA A CC 1.6 GSI	05/88 - 03/92	79,00	56 1405 0000 57 1405 0000	IN EX	4 4		1
X 16 SZ	1598	4	52 KW 71 PS	ASTRA F 1.6 i	05/93 - 07/96	79,00	56 1405 0000 57 1405 0000	IN EX	4 4		1
X 16 SZR	1598	4	55 KW 75 PS	ASTRA F CLASSIC CC 1.6 i ASTRA G 1.6 VECTRA B 1.6 i	01/98 - 01/05 02/98 - 09/00 10/95 - 04/02	79,00	56 1405 0000 57 1405 0000	IN EX	4 4		1
Z 16 SE	1598	4	64 KW 87 PS	ASTRA G 1.6 COMBO 1.6 CORSA C 1.6 MERIVA 1.6	09/00 - 04/05 10/01 - 09/00 - 12/09 05/03 - 05/10	79,00	56 1405 0000 57 1405 0000	IN EX	4 4		1

	IN/EX			Material Specification	Valve Stem Coating	Cotter Design	Seat Treatment	Tip Treatment
<b>1</b>								
	IN	56 1405 0000	L = 101,50 D = 38,00 d = 7,00 a = 45°	S	CR			H
	EX	57 1405 0000	L = 101,70 D = 31,00 d = 6,99 a = 45°	A/S	CR			H