












Globally reliable

# NEWSLETTER V1/2



	ccm 						IN/EX	QTY	Info	Pos.	
OM 654.820	1992	4	147-200 KW 200-272 PS	C-KLASSE C 220 d, C 300 d CLS 300/350 D EQ BOOST 4-MATIC E 300 d 4-matic, E 350 D EQ BOOST 4-MATIC GLE 300 d EQ Boost 4-matic	03/21 - 01/21 -  01/21 - 06/21 -	82,00	147 010 0017 00	IN	8		1
OM 654.920	1950	4	84-235 KW 114-320 PS	A-KLASSE A 180 d, A 200 d, A 220 d 4-matic B-KLASSE B 180 d, B 200 d, B 220 d C-KLASSE C 300 de, C 220 d, C 200 d, C 300 d CLA 180 d, 200 d, 220 d CLS 220 d, 300 d E-KLASSE E 200 d, E 220 d, E 300 d, E 300 de 4-matic GLA 200 d, GLA 180 d, GLA 220 d GLB 180 d, GLB 200 d, GLB 220 d GLC 200 d, 220 d, 300 d, 300 de GLE 300 d 4-matic, GLE 350 de 4-matic MARC POLO Camper 200 CDI, 220 CDI, 250 CDI, 300 CDI SPRINTER 3-t, 3,5-t, 4-t 211 CDI, 217 CDI, 311 CDI, 315 CDI, 417 CDI VITO 114 CDI, 116 CDI, 119 CDI, 124 CDI V-KLASSE V 220 CDI / d, V 250 CDI / d, V 300 CDI / d	11/18 - 12/18 - 04/18 - 04/19 - 04/18 - 01/16 - 02/20 - 08/19 - 04/19 - 10/18 - 03/19 - 06/20 - 04/20 - 03/19 -	82,00	147 010 0017 00 148 010 0018 00 148 010 0019 00	IN EX EX	8 8 8	For OE no. A 654 050 38 00  For OE no. A 654 050 10 00	2
OM 656.929	2925	6	183-250 KW 249-340 PS	CLS 350 d, CLS 400 d E-KLASSE E 350 d, E 400 d G-KLASSE G 350 d 4-matic, G 400 d 4-matic GLC 400 d 4-matic GLE 350 d 4-matic, GLE 400 d 4-matic GLS 350 d 4-matic, 400 d 4-matic S-KLASSE S 350 d, S 400 d	12/17 - 08/18 - 01/19 -  08/19 - 12/18 - 04/19 - 07/17 -	82,00	147 010 0017 01 148 010 0019 01	IN EX	12 12		3

	IN/EX			Material Specification	Valve Stem Coating	Cotter Design	Seat Treatment	Tip Treatment
<b>1</b>								
	IN	147 010 0017 00	L = 106,80 D = 28,45 d = 6,00 a = 45°		CR			
<b>2</b>								
	IN	147 010 0017 00	L = 106,80 D = 28,45 d = 6,00 a = 45°		CR			
	EX	148 010 0018 00	L = 106,38 D = 24,60 d = 6,00 a = 45°	A/S	CR			
	EX	148 010 0019 00	L = 106,20 D = 24,60 d = 6,00 a = 45°	A/S	CR			
<b>3</b>								
	IN	147 010 0017 01	L = 106,80 D = 28,45 d = 6,00 a = 45°		CR			
	EX	148 010 0019 01	L = 106,20 D = 24,60 d = 6,00 a = 45°	A/S	CR			